



SAFETY DATA SHEET

MA Multi Anchor comp A

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA Multi Anchor comp A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier G&B Fissaggi Srl
 Corso Savona 22
 10029, Villastellone (TO)
 Italy
 +39 011 96 19 433
 +39 011 96 19 382/ 639

Web www.gebfissaggi.com

Contact person info@gebfissaggi.com

1.4. Emergency telephone number

Emergency telephone +39 011 96 19 433 (8.30 - 12.30 /13.30 - 17.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Repr. 2 - H361d STOT RE 2 - H373
Environmental hazards	Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.

MA Multi Anchor comp A

Precautionary statements	<p>P260 Do not breathe vapours.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>
Contains	STYRENE
Supplementary precautionary statements	<p>P233 Keep container tightly closed.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Labelling notes	<p>The product is not flammable.</p> <p>On basis of test data.</p> <p>UN Test N.1 and ASTM D4359-90</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

STYRENE		5-10%
CAS number: 100-42-5	EC number: 202-851-5	REACH registration number: 01-2119457861-32
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H335 STOT RE 1 - H372 Asp. Tox. 1 - H304		
TITANIUM DIOXIDE		>0.5 <1.0%
CAS number: 13463-67-7	EC number: 236-675-5	
Classification Not Classified		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes.

4.2. Most important symptoms and effects, both acute and delayed

MA Multi Anchor comp A

Inhalation	May cause respiratory irritation.
Ingestion	May cause discomfort if swallowed.
Skin contact	May cause irritation.
Eye contact	May irritate eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion products Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid breathing vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from oxidising materials, heat and flames.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

MA Multi Anchor comp A

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

STYRENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 430 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 1080 mg/m³

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

WEL = Workplace Exposure Limit

STYRENE (CAS: 100-42-5)

DNEL Industry - Inhalation; Long term systemic effects: 85 mg/m³
 Industry - Inhalation; Short term systemic effects: 289 mg/m³
 Industry - Inhalation; Short term local effects: 306 mg/m³
 Industry - Dermal; Long term systemic effects: 406 mg/kg/day
 REACH dossier information

PNEC - Fresh water; 0.028 mg/l
 - marine water; 0.0028 mg/l
 - Intermittent release; 0.04 mg/l
 - STP; 4 mg/l
 - Sediment (Freshwater); 0.614 mg/kg
 - Sediment (Marinewater); 0.0614 mg/kg
 - Soil; 0.2 mg/kg
 REACH dossier information

TITANIUM DIOXIDE (CAS: 13463-67-7)

DNEL Industry - Inhalation; Long term systemic effects: 10 mg/m³
 REACH dossier information

PNEC - Fresh water; 0.127 mg/l
 - marine water; 1.0 mg/l
 - Intermittent release; 0.61 mg/l
 - STP; 100 mg/l
 - Sediment (Freshwater); 1000 mg/kg
 - Sediment (Marinewater); 100 mg/kg
 - Soil; 100 mg/kg
 REACH dossier information

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

MA Multi Anchor comp A

Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid.
Colour	Beige.
Odour	Aromatic.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not applicable.
Vapour density	Not determined.
Relative density	1.65 - 1.75 @ 20°C
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water
Partition coefficient	Not determined.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	No information available.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

MA Multi Anchor comp A

Reactivity The following materials may react with the product: Organic peroxides/hydroperoxides.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Organic peroxides/hydroperoxides.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 110.4

Specific target organ toxicity - repeated exposure

Target organs Causes damage to hearing organs through prolonged or repeated exposure via inhalation

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

Skin contact May cause irritation.

Eye contact May cause eye irritation.

Acute and chronic health hazards May cause skin irritation. May cause eye irritation. Gas or vapour is harmful on prolonged exposure or in high concentrations. May cause damage to organs (Hearing organs) through prolonged or repeated exposure if inhaled. May damage the unborn child.

Route of exposure Inhalation Skin and/or eye contact.

Toxicological information on ingredients.

STYRENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rat

MA Multi Anchor comp A

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

TITANIUM DIOXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Ecological information on ingredients.

STYRENE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 10 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 4.7 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 4.9 mg/l, Selenastrum capricornutum

TITANIUM DIOXIDE

Acute aquatic toxicity

Acute toxicity - fish LC₀, >: 1000 mg/l, Leuciscus idus (Golden orfe)
REACH dossier information

Acute toxicity - aquatic invertebrates NOEC, > 48 hours: 3 mg/l, Daphnia magna
REACH dossier information

Acute toxicity - microorganisms EC₅₀, > 3 hours: 1000 mg/l, Activated sludge
REACH dossier information

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

MA Multi Anchor comp A

Mobility Not applicable.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

MA Multi Anchor comp A

Inventories

EU - EINECS/ELINCS

STYRENE

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

SECTION 16: Other information

General information	The product is not flammable. On basis of test data. UN Test N.1 and ASTM D4359-90
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	13/01/2020
Version number	2.000
Supersedes date	25/04/2016
SDS number	20768
Hazard statements in full	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H361d Suspected of damaging the unborn child. H372 Causes damage to organs (Hearing) through prolonged or repeated exposure if inhaled. H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET

MA Multi Anchor comp B

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA Multi Anchor comp B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Catalyst.

1.3. Details of the supplier of the safety data sheet

Supplier G&B Fissaggi Srl
 Corso Savona 22
 10029, Villastellone (TO)
 Italy
 +39 011 96 19 433
 +39 011 96 19 382/ 639

Web www.gebfissaggi.com

Contact person info@gebfissaggi.com

1.4. Emergency telephone number

Emergency telephone +39 011 96 19 433 (8.30 - 12.30 /13.30 - 17.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Human health May cause skin disorders if contact is repeated or prolonged. The product is irritating to eyes and skin.

Environmental The product contains a substance which is very toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical Not considered to be a significant hazard due to the small quantities used.

2.2. Label elements

Hazard pictograms



Signal word Warning

MA Multi Anchor comp B

Hazard statements	H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H410 Very toxic to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Contains	BENZOYL PEROXIDE
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Labelling notes	On basis of test data. Solid - ASTM D4359-90

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BENZOYL PEROXIDE			10-15%
CAS number: 94-36-0	EC number: 202-327-6	REACH registration number: 01-2119511472-50	
M factor (Acute) = 10	M factor (Chronic) = 10		
Classification			
Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410			
BENZOIC ACID,NONYL ESTER,BRANCHED AND LINEAR			5-10%
CAS number: 670241-72-2	EC number: 447-010-5	REACH registration number: 01-0000018876-55	
Classification			
Aquatic Chronic 2 - H411			
ZINC DISTEARATE			1-5%
CAS number: 557-05-1	EC number: 209-151-9	REACH registration number: 01-2119982400-42	
M factor (Acute) = 1			
Classification		Classification (67/548/EEC or 1999/45/EC)	
Aquatic Acute 1 - H400		-	

MA Multi Anchor comp B

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion	May cause discomfort if swallowed.
Skin contact	Causes skin irritation.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	No specific firefighting precautions applicable when small quantities are involved in the fire.
Hazardous combustion products	Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment.
----------------------------------	-----------------------------------

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.
--------------------------------	--

6.4. Reference to other sections

MA Multi Anchor comp B

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from flammable and combustible materials. Store at temperatures between 5°C/41°F and 25°C/77°F.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

WEL = Workplace Exposure Limit

BENZOYL PEROXIDE (CAS: 94-36-0)

DNEL Industry - Oral; Long term : 1.6 mg/kg/day
Industry - Inhalation; Long term : 11.75 mg/m³
Industry - Dermal; Long term : 6.6 mg/kg/day

PNEC - Sediment (Freshwater); 0.338 mg/kg
- STP; 0.35 mg/l
- Sediment (Marinewater); 0.0338 mg/kg
- Fresh water; 0.000602 mg/l
- marine water; 0.0000602 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Nitrile rubber.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

MA Multi Anchor comp B

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. Do not smoke in work area.

Respiratory protection No specific recommendations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid.
Colour	Black.
Odour	Characteristic.
Odour threshold	Not determined.
pH	5 - 6
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.5 - 1.6
Bulk density	Not applicable.
Solubility(ies)	Not determined.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	>50°C
Viscosity	> 60 S ISO2431
Explosive properties	No information available.
Oxidising properties	Not determined.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Acids. Alkalis. Amines. Strong reducing agents.

10.2. Chemical stability

MA Multi Anchor comp B

Stability Stable at normal ambient temperatures and when used as recommended. Will decompose at temperatures exceeding 50°C.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with strong reducing agents. Avoid heat. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials to avoid Strong reducing agents. Acids, non-oxidising. Acids - organic. Alkalis - inorganic. Alkalis - organic. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation Sensitising.

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Route of exposure Skin and/or eye contact

Medical symptoms Skin irritation. Irritation of eyes and mucous membranes.

Medical considerations No information available.

Toxicological information on ingredients.

BENZOYL PEROXIDE

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

BENZOYL PEROXIDE

Acute aquatic toxicity

LE(C)₅₀ 0.01 < L(E)C50 ≤ 0.1

M factor (Acute) 10

Acute toxicity - fish LC50, 96 hours: 0.06 mg/l, Oncorhynchus mykiss (Rainbow trout)

MA Multi Anchor comp B

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 0.11 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 0.07 mg/l, Selenastrum capricornutum
<u>Chronic aquatic toxicity</u>	
M factor (Chronic)	10

BENZOIC ACID,NONYL ESTER,BRANCHED AND LINEAR

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 24 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) LC ₅₀ , 48 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) LC ₅₀ , 72 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) EC ₅₀ , 96 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) EC ₁₀₀ , 96 hours: > 1.23 mg/l, Cyprinus carpio (Common carp) NOEC, 96 hours: > 1.23 mg/l, Cyprinus carpio (Common carp)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 24 hours: > 2.2 mg/l, Daphnia magna EC ₅₀ , 48 hours: > 2.2 mg/l, Daphnia magna NOEC, 48 hours: > 2.2 mg/l, Daphnia magna
Acute toxicity - microorganisms	IC ₅₀ , 3 hours: > 1000 mg/l, Activated sludge NOEC, 3 hours: > 1000 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility Mobile. The product is partly miscible with water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Dispose of waste product or used containers in accordance with local regulations
Disposal methods	Dispose of waste via a licensed waste disposal contractor.
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3077
UN No. (IMDG)	3077

MA Multi Anchor comp B

UN No. (ICAO) 3077

UN No. (ADN) 3077

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS BENZOYL PEROXIDE, BENZOIC ACID,NONYL ESTER,BRANCHED AND LINEAR)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS BENZOYL PEROXIDE, BENZOIC ACID,NONYL ESTER,BRANCHED AND LINEAR)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS BENZOYL PEROXIDE, BENZOIC ACID,NONYL ESTER,BRANCHED AND LINEAR)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS BENZOYL PEROXIDE, BENZOIC ACID,NONYL ESTER,BRANCHED AND LINEAR)

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID classification code M7

ADR/RID label 9

IMDG class 9

ICAO class/division 9

ADN class 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

ADR transport category 3

Emergency Action Code 2Z

Hazard Identification Number (ADR/RID) 90

Tunnel restriction code (-)

MA Multi Anchor comp B

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

SECTION 16: Other information

General information	On basis of test data. Solid - ASTM D4359-90
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	13/01/2020
Version number	3.000
Supersedes date	05/12/2017
SDS number	20769
Hazard statements in full	H241 Heating may cause a fire or explosion. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.