

Technical Instruction Sheet

page 1 of 1

- Characteristics:** AKEMI® Oil and Grease Remover Paste is a product which contains solvents and special absorbent substances. It is characterized by the following properties:
- suitable for all kinds of natural and artificial stone
 - extremely effective, even in case of intensive staining
 - does not contain acids, leaching agents, waxes, resins or silicones
 - low odour
 - has a pliant, creamy consistency and can therefore also be easily applied to smooth and polished surfaces and has a good adhesion on the surface
- Field of Application:** AKEMI® Oil and Grease Remover Paste is used on all kinds of natural and artificial stone to remove grease, oil and wax stains as well as discolouration in border areas resulting from plasticizers in sealing materials.
- Instructions for Use:**
1. Surfaces to be treated must be dry.
 2. In the case of discolouration in border areas, the sealant must be removed thoroughly from the joint.
 3. Apply AKEMI® Oil and Grease Remover Paste with a brush or spatula (1-2 mm layer at least); recommended working temperature: 5-25°C (41-77°F).
 4. After drying (approx. 30 – 60 min.), the residue must be swept off, sucked off or wiped away.
 5. In the case of intensive staining and if required, the procedure is to be repeated (several times if necessary).
 6. It is recommended to apply AKEMI® Stone Cleaner as a final cleaning measure.
- Special Hints:**
- You should use AKEMI® Liquid Glove to protect your hands when working with the product.
 - It is recommended to test the effect of the product on an inconspicuous area first.
 - In order to ensure orderly disposal, the tube must be emptied completely.
- Safety Measures:** see EC Safety Data Sheet
- Technical Data:**
- | | |
|-------------|---|
| Colour: | light grey |
| Density: | 1.40 g/cm ³ |
| Shelf life: | 2 years if stored in cool place free from frost in its tightly closed original container. |
- Notice:** The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TIS 09.13